



Energy Efficient Design
Diseño Eficiente de la Energía
Conception rationnelle de l'énergie

Thermoplastic Sump Pump

High-Output Performance

Thermoplastic construction

Resists corrosion

Zinc motor housing

Dissipates heat quickly and extends motor life

Stainless steel fasteners and hardware

Superior quality

Smooth Flow Hydraulics™

Deliver high performance for demanding applications

Vertical float switch

Operates in 10" basins or larger



1/3 HP 3600 GPH
FPZS33V

1/2 HP 4200 GPH
FPZS50V

3/4 HP 4700 GPH
FPZS75V

PERFORMANCE (GPH)							FLOAT SWITCH		SOLIDS HANDLING
DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	5'	10'	15'	20'	MAX. LIFT	ON	OFF	
FPZS33V	3,600	3,060	2,400	1,680	660	22'	7.5"	3"	3/16"
FPZS50V	4,200	3,660	3,000	2,160	960	22'	7.5"	3"	3/16"
FPZS75V	4,700	4,200	3,540	2,820	1,800	24'	7.5"	3"	3/16"

MODEL	WARRANTY	UPC	CARTON DIMENSIONS	PALLET QTY.	WEIGHT
FPZS33V	1 YEAR	022315368477	8" x 6" x 12.75"	105	7.7 LBS.
FPZS50V	1 YEAR	022315368491	8" x 6" x 12.75"	105	10 LBS
FPZS75V	1 YEAR	022315368507	8" x 6" x 12.75"	105	10 LBS

Includes: 1 1/2" NPT discharge, 8' grounded power cord, piggyback-style switch for automatic or manual operation, detailed owner's manual

Check Valve replacement is recommended

293 Wright Street, Delavan, WI 53115

For Questions or Installation Instructions:

www.flotecwater.com 1-800-365-6832

